





ZAMUS STAR

E-STAR

U-WING


■ Tolerance


All Sizes

0~-0.04

Shank Dia

h6















## ZAMUS THUNDER

X-STAR

S-WING

ALU-WAVE

STANDARD

COPPER MATE

GRA MATE

# CARBIDE









					All Sizes				
EDP No	SIZES (mm)								
	D	R	L1	L2	D2				
TXB302 010	1	0.5	2	50	4				
TXB302 015	1.5	0.75	3	50	4				
TXB302 020	2	1	4	50	4				
TXB302 025	2.5	1.25	6	50	4				
TXB302 030	3	1.5	6	50	4				
TXB302 040	4	2	8	50	4				
TXB302 050	5	2.5	10	50	6				
TXB302 060	6	3	12	50	6				
TXB302 080	8	4	14	60	8				
TXB302 100	10	5	18	75	10				
TXB302 120	12	6	22	75	12				
TXB302 140	14	7	32	75	14				
TXB302 160	16	8	32	100	16				
TXB302 180	18	9	32	100	18				
TXB302 200	20	10	38	100	20				

### ■ Applicable Working Material

Carbon Steel ~ HB225	Alloy Steel HB225~325	Prehardened Steel HRc30~50	Hardened Steel		_		Cast Iron		Stainless
			SKD61 ~HRc55	SKD11 HRc55~	Copper	Graphite	~FCD500	Aluminum	Steel
©	0	0							