

NC spotting drill plain shank

$\geq \emptyset$ 6 mm with drive flat to DIN 1835-B.

 $Precision\ centred\ ground\ point\ with\ thin\ chisel\ edge-gives\ easy\ spot\ drilling\ and\ high$ accuracy of the centre hole form. Very sturdy due to short flutes.


11 2060 - High-performance NC spotting drill.

Tool substrate made of sintered powder metallurgy for applications demanding high standards of tool life and accurate centring. Very good wear resistance in stainless steels.

Note: Use speed for the actual hole \varnothing (not necessarily the speed for the drill outer \varnothing).







| Suitable for/ v _c [m/min] | Alu plastics | Alu Æ | Alu cast > 10 % Si | <u>I</u> < 500 N | | ∑ <900 N | <u>II</u> < 1100 N | < 1400 N | < 55 HRC | < 60 HRC | ∑ | < 67 HRC | INOX < 900 N | INOX > 900 N | Ti > 850 N | GG(G) | CuZn | Uni | 6 | \ | 1 | * | |
|---|-----------------|----------|--------------------------|---------------------|----|-------------|-----------------------|--------------|--------------|--------------|---|--------------|-----------------|-----------------|------------|-------|------|-----|---|----------|----------|---|---------|
| ISO code | N | N | N | P | P | P | P | P | Н | Н | Н | Н | M | M | S | K | N | | | | | | |
| 11 2000 | 70 | 45 | | 40 | 30 | 25 | 10 | 8 | | | | | 12 | 8 | | | 80 | • | | | | | |
| 11 2020/2100 | 87 | 56 | 50 | 50 | 37 | 31 | 12 | 10 | | | | | 15 | 10 | 6 | 31 | 100 | • | | | | | |
| 11 2060 | 96 | 62 | 55 | 55 | 42 | 35 | 14 | 12 | | | | | 18 | 13 | 8 | 35 | 112 | • | • | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |

HSS-É

 $ØD_ch6$ **11 2000 | ≦ 11 2020 | ≦ 11 2060 | ≦** | NC spotting drill HSS-E-PM NC spotting drill NC spotting drill HSS-E

 $ØD_s$ I < 900 N

| | | 90 | ° N | | | 11 2000 11 2020 11 2060 | 11 2100 | | |
|----|-------|-------|-------|-------|----|-------------------------------|---------|----|---------|
| mm | | TiAIN | TIAIN | TIAIN | mm | mm | mm | mm | mm/rev. |
| 3 | eShop | eShop | eShop | eShop | 12 | 46 | 80 | 3 | 0.03 |
| 4 | eShop | eShop | eShop | eShop | 12 | 55 | 100 | 4 | 0.03 |
| 5 | eShop | eShop | eShop | eShop | 15 | 60 | 120 | 5 | 0.04 |
| 6 | eShop | eShop | eShop | eShop | 20 | 66 | 140 | 6 | 0.05 |
| 8 | eShop | eShop | eShop | eShop | 25 | 79 | 140 | 8 | 0.07 |
| 10 | eShop | eShop | eShop | eShop | 25 | 89 | 170 | 10 | 0.07 |
| 12 | eShop | eShop | eShop | eShop | 30 | 102 | 170 | 12 | 0.07 |
| 16 | eShop | eShop | eShop | eShop | 35 | 115 | 200 | 16 | 0.07 |
| 20 | eShop | eShop | eShop | eShop | 40 | 131 | 200 | 20 | 0.07 |

| E Ctandowd N 110 1 000 D | HSS E | Standard | Type N | h6 | 90° | h6 DIN 1835 |
|--------------------------|----------|----------|-----------|----|-----|-------------------|
|--------------------------|----------|----------|-----------|----|-----|-------------------|

Garant NC spotting drill sets

With drive flats to DIN 1835-B. Precision centred ground point with thin chisel edge – gives easy spot drilling and high accuracy of the centre hole form. Very sturdy due to short flutes.

Supplied with: 4-piece set of NC spotting drills in a plastic box.

Note: Use speed for the actual hole \varnothing

(not generally the speed for the drill outer \varnothing).

| Туре | | | 6-12 |
|-----------------------------|---|-------|--------------------|
| ≦ 11 2107 | NC spotting drill HSS-E No. 112000 with plastic box 90° | | eShop |
| ≦ 11 2108 | NC spotting drill HSS-E No. 112020 with plastic box 90° | TiAIN | eShop |
| Content: 1 each NC spotting | drills | | Size 6; 8; 10; 12. |

