



TX304H 4 Flutes 45° Helix Square End Mill


Endmill



► Tolerance

DC		Shank Dia
Ø3	-0.014 ~ -0.028	
Ø4 ~ Ø6	-0.02 ~ -0.038	
Ø8 ~ Ø10	-0.025 ~ -0.047	
Ø12 ~ Ø18	-0.032 ~ -0.059	
Ø20 ~	-0.04 ~ -0.073	

h6



EDP No	DC	APMX	OAL	DCONMS
TX304H 030	3	8	50	6
TX304H 030S3	3	8	50	3
TX304H 030S4	3	8	50	4
TX304H 040	4	11	50	6
TX304H 040S4	4	11	50	4
TX304H 050	5	13	50	6
TX304H 060	6	13	50	6
TX304H 080	8	19	60	8
TX304H 100	10	22	70	10
TX304H 120	12	26	75	12
TX304H 130	13	26	80	12
TX304H 140	14	26	80	14
TX304H 160	16	32	90	16
TX304H 180	18	32	100	18
TX304H 200	20	38	100	20

Zamus Star

E-Star

U-Wing

Zamus Thunder

X-Star

S-Wing

A-Wing

Standard

Copper -Mate

Gra -Mate

► Applicable Working Material

○ : GOOD ◎ : EXCELLENT

H		P			K	N			M	S
Hardened Steel		Carbon Steel	Alloy Steel	Prehardened Steel	Cast Iron	Copper	Graphite	Aluminum	Stainless Steel	Heat Resistant Alloy
SKD61 ~HRc55	SKD11 HRc55~	~HB225	HB225 ~325	HRc30~50	~FCD500					
		◎	◎	○						